

Bridgeport BTS-M-RC ISO 6



View online: <https://www.biofit.com/product/bridgeport-series-technical-chair-steel-base-medium-seat-height-iso-6-bl/58>



This bench height Bridgeport Series chair features an ISO 6 clean room performance package with Grade 2 blue vinyl upholstery. Components are highlighted by a comfy ergonomic seat, nimble trapezoid-shaped backrest and durable steel base with affixed footring. Ships in 2 business days.

Manuf Code: BTS-M-RC-T-XF-XA-ISO6-2DS-P28542

Recommended For: clinical research, medical applications, multiple science disciplines

Use In: laboratories, technical settings



Available via standard shipping



Key Features

Height Compatibility: High Bench (H)

Seat Size: Small

Back Size: Small

Base: Steel / Tubular Steel

Finish Color: Chrome

Seat-Height Adjustable Range (in.): 21-28

ISO Clean Room Standard: ISO 6

Upholstery Type & Color: Grade 2 Blue Vinyl
P28542

Recommended User Height: for work surfaces 33" to 40"

Seat Description: Concave upholstered seat with internal seat board bumperguard; measures 18.5" wide x 16.5" deep x 3" thick.

Back Description: Streamlined upholstered backrest with lumbar support and plastic protective panel; measures 14.5" wide x 9.5" high.

Control Description: Control allows function of the seat height activation and backrest adjustments by means of easily engaged levers which can be activated from the seated position. Seat tilt is fixed at 3.5° rearward while the backrest adjusts 8° forward and 13° rearward.

Base Description: Small, five-legged base with caster-to-caster diameter of 23.0" and maximum width of 22.8". Welded 1" x 14-gauge steel tubular legs withstand test loads of 2X BIFMA strength requirements. Features standard 50mm, steel-reinforced, tapered hub, and a 21" affixed steel tubular footring welded to top of legs at 8" above floor height. A reinforced nylon insert at the end of each leg accepts a caster or glide stem. The welds at the hub are concealed by a two-piece, polypropylene cover.

Footring Description: Includes 21" affixed steel tubular footring welded to top of legs.

Caster Glide Description: Two inches in height, with dual soft-wheels. Casters resist movement when the seat is unoccupied. Plastic collar around caster stem to match base. Standard casters have grey tread.

Specifications

Weight: 40.0 lbs

Dimensions: 23" x 23" x 34"

Seat Width (in.): 18.5

Seat Depth (in.): 16.5

Seat Cushion Thickness (in.): 3

Back Width (in.): 14.5

Back Height (in.): 9.5

Footring Diameter (in.): 21

Fire Retardancy Standards: CAL117

Weight Capacity: 300

Additional Info

Bridgeport Series seating outfitted with critical use performance packages are engineered for use in technical environments in a variety of industries.

This chair features an ISO 6 clean room performance package and is designed for use at 33"-40" high benches. Features include easy pneumatic seat height adjustments from 21" to 28", an ergonomic, concave seat with internal seat board bumperguard, a trapezoid shaped back with lumbar support and a plastic protective panel, and convenient backrest tilt and height adjustments. The seat and back are covered with Grade 2 blue vinyl upholstery for durability and easy-cleaning. The chair rests on a rugged 23" diameter tubular steel base with affixed 21" diameter footring, and dual-wheel, non-marring polyurethane casters that resist movement when the chair is unoccupied. Chrome finish on metal parts.

It is available on BioFit's 2 Day Ship (2DS) program for fast delivery in quantities up to 15 chairs.

Complies with product safety and performance standards guidelines as established by the American National Standards Institute (ANSI) and Business and Institutional Furniture Manufacturers' Association (BIFMA). Meets CAL 117 fire retardant standards. LEED compliant.

Backed by a 13-year warranty with lifetime warranty on pneumatics.

Your BioFit Sales Representative

Mark Romey

800-365-6465 **office**
info@westrepenenterprises.com

Contact BioFit

BioFit Customer Service

Customer Service: (800) 597-0246
Online: <https://www.biofit.com/contact>

Office Address:

15500 BioFit Way
Bowling Green, OH 43402

Mailing Address:

PO Box 109
Waterville, OH 43566