Elite EES-M-RC ISO 8



View online: https://www.biofit.com/product/elite-series-technical-chair-steel-base-medium-seat-height-iso-8-clean-r/303



This bench height Elite Series chair features an ISO 8 clean room performance package with Grade 2 black vinyl upholstery. Components include a mid-sized adjustable seat, ergonomic functionality, a back engineered for all-day comfort, and a steel base with affixed footring.

Manuf Code: EES-M-RC-T-XF-XA-ISO8-P28540

Recommended For: ISO 8 clean rooms

Use In: ISO 8 clean rooms, technical settings



Available via standard shipping



Key Features

Height Compatibility: Standard Bench (M) Finish Color: Black Powdercoat

Seat Size: Medium Seat-Height Adjustable Range (in.): 21-28

Back Size: Medium ISO Clean Room Standard: ISO 8

Base: Steel / Tubular Steel Upholstery Type & Color: Grade 2 Black Vinyl

P28540

Recommended User Height: for work surfaces 33" to 40"

Seat Description: Ergonomic upholstered seat with four-way contouring and internal seat board bumperguard; measures 18.5" wide x 17" deep x 3" thick.

Back Description: Upholstered backrest with lumbar support and plastic protective panel; measures 15.5" wide x 14.5" high.

Control Description: Control allows function of the seat height activation and backrest adjustments by means of easily engaged levers which can be activated from the seated position. Seat tilt is fixed at 3.5° rearward while the backrest adjusts 8° forward and 13° rearward.

Base Description: Small, five-legged base with caster-to-caster diameter of 23.0" and maximum width of 22.8". Welded 1" x 14-gauge steel tubular legs withstand test loads of 2X BIFMA strength requirements. Features standard 50mm, steel-reinforced, tapered hub, and a 21" affixed steel tubular footring welded to top of legs at 8" above floor height. A reinforced nylon insert at the end of each leg accepts a caster or glide stem. The welds at the hub are concealed by a two-piece, polypropylene cover.

Footring Description: Includes 21" affixed steel tubular footring welded to top of legs.

Caster Glide Description: Two inches in height, with dual soft-wheels. Casters resist movement when the seat is unoccupied. Plastic collar around caster stem to match base. Standard casters have grey tread.

Specifications

Weight: 43.0 lbs Back Width (in.): 15.5

Dimensions: 23 x 23 x 39 Back Height (in.): 14.5

Seat Width (in.): 18.5 Footring Diameter (in.): 21

Seat Depth (in.): 17 Fire Retardancy Standards: CAL117

Seat Cushion Thickness (in.): 3 Weight Capacity: 300



Additional Info

Elite Series seating models outfitted with critical use performance packages are engineered for use in techincal enviornments in a variety of industries.

The chair features an ISO 8 clean room performance package and is designed for the use in 33" - 40" bench height. Features include easy pneumatic seat height adjustments from 21" - 28", an ergonomic seat with four-way contouring and internal seat board bumperguard, a mid-sixed back with lumbar support and a plastic portective panel, and convenient backrest tile and height adjustments. The seat and back are covered with Grade 2 black vinyl upholstery. The chair rests on a durable 23" diameter tubular steel base with affixed 21" diameter footring and dual-wheel, non-marring polyurethane casters that resist movement whenthe chair is upoccupied. Metal parts have chrome finish. Compents packaged under laminar flow clean room hood.

Complies with product safety and performance standards guidelines as established by the American National Standards Institute (ANSI) and Business and Institutional Furniture Manufacturer's Association (BIFMA). Meets CAL 117 fire retardant standards. LEED compliant.

Backed by a 13-year warranty with lifetime warranty on pneumatics.

Your BioFit Sales Representative

Contact BioFit

Mark Romey

800-365-6465 office

info@westrepenterprises.com

BioFit Customer Service

Customer Service: (800) 597-0246
Online: https://www.biofit.com/contact

Office Address:

15500 BioFit Way

Bowling Green, OH 43402

Mailing Address:

PO Box 109

Waterville, OH 43566

