

Model

Horizon Series™ HLR104-ADA Undercounter Laboratory/Pharmacy Refrigerator

Specifications

Application, Rating and Electrical Data	
Application	Storage of medical and scientific products
Storage Volume	4 cu ft (113 L)
Temperature Range	2° to 10°C
Electrical Power	115V 60Hz
Maximum Current	5 FLA
Building Supply Rating	15 amp dedicated ground circuit
Power Plug / Power Cord Length	NEMA 5-15 hospital grade plug (115V) 8-10 ft (2439-3048 mm)
Certification / Agency Listing	QPS (Certified to UL and CSA Standards)
Indoor/Outdoor Use	Indoor use only
Application Environment	Non-corrosive, non-flammable, non-explosive, 15°C to 32°C (59°F to 90°F)
Refrigeration System	
Refrigeration System	Forced-air circulation
Compressor / Number	.17 HP (115V) hermetic / 1
Condenser Type / Number	Air-cooled fin and tube / 1
Expansion Device	Cap tube
Evaporator Type	Air-cooled fin and tube
Defrost Method	Automatic
Refrigerant Charge	R134A Non-CFC
Performance Data	
Uniformity	+/-1.5°C at 4°C Setpoint
Warranty	
Rel.i™ (US/Canada)	5 years compressor, 2 years parts, 1 year labor
Outside US/Canada	Consult your local representative

Controller	
Interface	LED digital display, °C or °F
Power Switch	On/Off
Controller Type	Microprocessor-based controller with alarm/ monitor
Security	Lockable door, optional keypad access
Control Sensor	RTD
High / Low Alarms	Fully adjustable
Door Ajar Alarm	Yes
Power Failure Alarm	Yes
Min/Max Display and Reset	Yes
Battery Back-up	9-volt non-rechargeable
Dimensions and Construction	
Interior (w x h x d)	19.5 x 17.75 x 22 in 496 x 451 x 559 mm
Exterior (w x h x d) (Includes leveling feet)	24 x 32 x 26.75 in 610 x 813 x 680 mm
Overall Exterior (w x h x d) (Includes door handle and leveling feet)	24 x 32 x 28.5 in 610 x 813 x 724 mm
ADA Compatible	Fits under 34" (864 mm) ADA compliant counters
Insulation	Sustainable, U.S. EPA and SNAP approved Ecomate®
Exterior / Interior Finish	Bacteria-resistant powder coating
Doors	1, Solid
Access Ports	Rear access port
Interior Storage / Capacity	2 epoxy coated shelves 18 x 18 in (458 x458 mm) 100 lb (46 kg) max capacity / shelf
Leveling Feet	Standard
Casters	Optional / swivel locking
Integrated Access Control	Optional - Electromagnetic lock via digital keypad
Net Weight	185 lb (84 kg)
Shipping Weight	250 lb (114 kg)
Clearance Requirements	Minimum of 3" (76mm) behind unit for clearance and feature access.
Options / Accessories	Chart Recorder, Stacking Kit, Floor & Wall Bracket Kit, Remote Alarms, Interior Light, Glass Door, Casters, Stainless Steel Interior and Exterior, Remote Lock Adapter Kit, Extended Warranty



Technical Data Sheet









